



Q2-AUTOMATIC TOP SEAL

Q2-Automatic Top Seal is designed to prevent solids from accumulating between the stationary barrel and bottom hold down. It will help to eliminate stripping jobs.

FEATURES

Q2-Automatic Top Seal contains a packing element bonded to a threaded steel insert, which eliminates damage to the pack-off when released from the tubing wall.

APPLICATION

- Bottom hold-down insert pumps.
- 2-3/8", 2-7/8" and 3-1/2" tubing strings.

SPECIFICATIONS

		Tubing Size	2-3/8"	2-7/8"	3-1/2"
Thread Size	Top End		1.4704-14	1.8024-14	2. 1095-11 1/2
	Bottom End		1.5730-16	2.0870-16	2.5730-16
Rubber Pack-Off OD			1.812"	2.250"	2.750"
Item	No Req'd	Description	Component Part Number		
A	1	Bushing	121K6	9N1	9Q1
B	1	Rubber Pack-Off	121K7	9N2	9Q2
C	1	Mandrel	121K1	121N1	121Q1
D	1	Bushing	121K2	121N2	121Q2
E	1	Body	121K3	121N3	121Q3
F	1	Brass Ring	121K5	121N5	121Q5
G	1	Plug	121K4	121N4	121Q4

1. Rubber Pack-Off material is 70A Hardness Nitrile Buna-N.
2. Ring material is Brass.
3. All other components parts are made of Carbon Steel and Monel.

